

Solenoids

3-Way Conduit Single Solenoid NAMUR Valve

- Cv = 1.68
- Ports 1/4" NPT
- Duty Cycle = 100% Continuous
- Power Consumption = 2.5 Watts
- Pressure Range = 20 to 120 PSIG
- Temperature Range = 35° to 130°F



MODEL	VOLTAGE	INRUSH
3TS3NC120	120 VAC	62 mA
3TS3NC24	24 VDC	108 mA
3TS3NC12	12 VDC	204 mA
3TS3NC220	220VAC	31 mA
3TS3NC24V	24 VAC	See*

*Consult Factory

3-Way Explosion Proof Single Solenoid NAMUR Valve

- Cv = 1.68
- Ports 1/4" NPT
- Duty Cycle = 100% Continuous
- Power Consumption = 4.6 Watts
- Pressure Range = 20 to 120 PSIG
- Temperature Range = 35° to 130°F



MODEL	VOLTAGE	INRUSH
3TS3NEX120	120 VAC	74 mA
3TS3NEX24	24 VDC	190 mA
3TS3NEX12	12 VDC	372 mA
3TS3NEX220	220VAC	36 mA

4-Way Conduit Single Solenoid NAMUR Valve

- Cv = 1.68
- Ports 1/4" NPT
- Duty Cycle = 100% Continuous
- Power Consumption = 2.5 Watts
- Pressure Range = 20 to 120 PSIG
- Temperature Range = 35° to 130°F



MODEL	VOLTAGE	INRUSH
3TS4NC120	120 VAC	62 mA
3TS4NC24	24 VDC	108 mA
3TS4NC12	12 VDC	204 mA
3TS4NC220	220VAC	31 mA
3TS4NC24V	24 VAC	See*

*Consult Factory

4-Way Explosion Proof Single Solenoid NAMUR Valve

- Cv = 1.68
- Ports 1/4" NPT
- Duty Cycle = 100% Continuous
- Power Consumption = 4.6 Watts
- Pressure Range = 20 to 120 PSIG
- Temperature Range = 35° to 130°F



MODEL	VOLTAGE	INRUSH
3TS4NEX120	120 VAC	74 mA
3TS4NEX24	24 VDC	190 mA
3TS4NEX12	12 VDC	372 mA
3TS4NEX220	220VAC	36 mA