

Model PVB4V

PRESSURE VACUUM BREAKER

Job Name:	Contractor:	
Job Location:	P.O. Number:	
Engineer:	Representative:	
Tag:	Wholesale Distributor:	

SPECIFICATIONS


The ½" - 2" Pressure Vacuum Breaker shall be an Apollo® Model PVB4V (formally Model PVB). The assembly shall be manufactured in America. The body will be bronze with a stainless-steel powder-coated canopy. The domestic shut-off ball valves shall incorporate stainless steel handles. The design will incorporate a spring-loaded relief valve to reduce the possibility of damage due to intermittent freezing conditions. The acetal check valve module will be replaceable. The pressure drop across the assembly shall be documented by USC's FCCC&HR approval curves. The assembly shall prevent contamination of potable water due to back-siphonage.

FEATURES

- Low pressure loss
- · Corrosion resistant
- Built-in freeze resistance
- · Compact yet easy to maintain
- One piece cap/float assembly
- · Removable integral check valve
- Apollo[®] ball valves w/ SS handles & nuts standard
- MADE IN THE USA



ORDERING INFORMATION



SIZE

3 - 1/2"	□ 4 - ¾"	□ 5 - 1
6 – 1 ¼"	□ 7 – 1 ½"	□ 8 – 2°

SHUT-OFF VALVES

- 1 Less ball valves
- ☐ 2 With Apollo® ball valves
- ☐ 4 With union-end Apollo® ball valves

OPTIONS

- □ LL Locking Lever Handles on Apollo® ball valves
- ☐ F SAE test cock threads
- *F available only in sizes 3/4" & 1"

APPROVALS

ASSE® 1020, CSA® B64.1.2, USC's FCCC&HR and IAPMO


PERFORMANCE RATING

Maximum Operating Pressure 150 psi Design Pressure 300 psi Temperature Range 33 °F – 180 °F



DIMENSIONS (in.)

ZZ.1313113 ()						
Size	Α	В	C	Wt. (lb.)		
1/2"	3 3/4	4 %	7 1/8	3.4		
3/4"	4 %	5 1/8	7 %	3.9		
1"	5 1/8	6 1/8	8 %	5.3		
1 ¼"	6 1/8	7	10 %	9.3		
1 ½"	6 1/4	7 %	10 %	12.2		
2"	6 1/8	7 1/8	12 1/8	23.3		



FLOW CURVES

