



Model 162T

CLASS 125 SWING CHECK

VITON SEAT, NPT

(61Y SERIES)

Job Name:	Contractor:
Job Location:	P.O. Number:
Engineer:	Representative:
Tag:	Wholesale Distributor:

Description

The Apollo Model 162T Swing Check provides a cost effective "made in the USA" alternative to globally sourced check valves. These valves are cast, machined, assembled, and tested in South Carolina. The Apollo Swing Check can be installed in both horizontal or vertical line with upward flow.

Features

- Renewable Seat Disc
- Soft Viton Seat
- Dezincification Resistant
- 100% Factory tested
- NPT Connection
- 100% machined and assembled in USA

Standards

- MSS SP-80, "Bronze Gate, Globe, & Check Valves",
- ASME B1.20.1, "Pipe Threads, General Purpose (Inch)"

Performance Rating

Saturated Steam: 67 psi (4.6 Bar) to 300°F(148°C)
Cold Working Pressure: 200 psi (13.8 Bar) at 100°F



Order Information

Size	Model	Item Number Thread (NPT)
<input type="checkbox"/> 1/4"	162T	61Y-201-V1
<input type="checkbox"/> 3/8"	162T	61Y-202-V1
<input type="checkbox"/> 1/2"	162T	61Y-203-V1
<input type="checkbox"/> 3/4"	162T	61Y-204-V1
<input type="checkbox"/> 1"	162T	61Y-205-V1
<input type="checkbox"/> 1-1/4"	162T	61Y-206-V1
<input type="checkbox"/> 1-1/2"	162T	61Y-207-V1
<input type="checkbox"/> 2"	162T	61Y-208-V1

Material Specifications

Part Name	Material
Body	ASTM B62 Bronze
Cap	ASTM B62 Bronze
Hanger	Stainless Steel
Pin	Stainless Steel
Seat	Viton®
Plug	Brass

Dimensions

Size	Height (in.)	Length (in.)	Weight (lbs)	Cv (gpm)
1/4"	1.51	2.14	.64	2.6
3/8"	1.51	2.14	.62	4.5
1/2"	1.65	2.48	.73	7.0
3/4"	1.9	2.94	1.06	12.0
1"	2.26	3.57	1.7	28.6
1-1/4"	2.99	4.50	3.3	39.0
1-1/2"	2.99	4.50	3.1	56.0
2"	3.74	5.25	5.4	152.0



Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28105 USA ; www.apollovalves.com ; 704-841-6000

Conbraco Industries can accept no responsibility for possible errors in this document and reserves the right to alter its product design or construction without notice and without incurring any obligation to make such changes on Conbraco products previously or subsequently sold. All product specifications are approximate and are provided for reference only.