



Model 164T

CLASS 150 SWING CHECK

BRONZE SEAT, NPT

(61Y SERIES)

Job Name:	Contractor:
Job Location:	P.O. Number:
Engineer:	Representative:
Tag:	Wholesale Distributor:

Description

The Apollo Model 164T Swing Check provides a cost effective "made in the USA" alternative to globally sourced check valves. These valves are cast, machined, assembled, and tested in South Carolina. The Apollo Swing Check can be installed in both horizontal or vertical line with upward flow.

Features

- Renewable Seat Disc
- Metal Seat
- Dezincification Resistant
- 100% Factory tested
- NPT Connection
- 100% machined and assembled in USA

Standards

- MSS SP-80, "Bronze Gate, Globe & Check Valves",
- ASME B1.20.1, "Pipe Threads, General Purpose (Inch)"

Performance Rating

Saturated Steam: 150 psi (10.4 Bar) to 366°F(185°C)
Cold Working Pressure: 300 psi (20.7Bar) at 100°F
Temperature Range: -20°F to 406°F



Order Information

Size	Model	Item Number Thread (NPT)
<input type="checkbox"/> 1/4"	164T	61Y-211-01
<input type="checkbox"/> 3/8"	164T	61Y-212-01
<input type="checkbox"/> 1/2"	164T	61Y-213-01
<input type="checkbox"/> 3/4"	164T	61Y-214-01
<input type="checkbox"/> 1"	164T	61Y-215-01
<input type="checkbox"/> 1-1/4"	164T	61Y-216-01
<input type="checkbox"/> 1-1/2"	164T	61Y-217-01
<input type="checkbox"/> 2"	164T	61Y-218-01
<input type="checkbox"/> 2-1/2"	164T	61Y-219-01
<input type="checkbox"/> 3"	164T	61Y-210-01

Material Specifications

Part Name	Material
Body	ASTM B62 Bronze
Cap	ASTM B62 Bronze
Hanger	Stainless Steel
Pin	Stainless Steel
Seat	ASTM B62 Bronze
Plug	Brass

Dimensions

Size	Height (in.)	Length (in.)	Weight (lbs)	Cv (gpm)
1/4"	1.51	2.14	.64	2.6
3/8"	1.51	2.14	.62	4.5
1/2"	1.65	2.48	.73	7.0
3/4"	1.9	2.94	1.06	12.0
1"	2.26	3.57	1.7	28.6
1-1/4"	2.99	4.5	3.4	39.0
1-1/2"	2.99	4.5	3.1	56.0
2"	3.74	5.25	5.5	152.0
2-1/2"	5.11	8.00	11.7	198.0
3"	6.05	9.24	17.8	242.0



Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28105 USA ; www.apollovalves.com ; 704-841-6000

Conbraco Industries can accept no responsibility for possible errors in this document and reserves the right to alter its product design or construction without notice and without incurring any obligation to make such changes on Conbraco products previously or subsequently sold. All product specifications are approximate and are provided for reference only.