


61-700 - Brass NPT "Mini" Check Valves (1/4" to 1")

Sizes: 1/4" to 1" Ends: NPT



Overview

Ideally suited for all OEM applications where space is a premium. Excellent use on water and alir. Features a buble-tight soft seat design with a very light load stainless steel spring. It is rated at 250 psig WOG with a maximum temperature of 180°F.



Dimensions

NOTE: Dimensions shown are subject to change. Contact factory for certified prints (exact dimensions) when required.

required.					
Size in./mm	A in./mm	B in./mm	C in./mm	Wt/100	Typical Cv Factors
1/4 8 6.35	1.72 43.69	0.81 20.57	0.92 23.37	22.00	0.78
3/8 10 9.53	1.79 45.47	0.93 23.62	1.05 26.67	29.00	1.81
1/2 15 12.70	2.02 51.31	1.06 26.92	1.17 29.72	38.00	5.13
3/4 20 19.05	2.50 63.50	1.25 31.75	1.40 35.56	54.00	10.51
1 25 25.40	2.95 74.93	1.62 41.15	1.76 44.70	110.00	14.25
	1/4 8 6.35 3/8 10 9.53 1/2 15 12.70 3/4 20 19.05	in./mm in./mm 1/4 8 1.72 8 6.35 1.79 9.53 1/2 1/2 15 12.70 2.02 51.31 3/4 20 19.05 2.50 63.50 1 2.95 74.93	in./mm in./mm in./mm 1/4 8 6.35 1.72 43.69 0.81 20.57 3/8 10 9.53 1.79 45.47 0.93 23.62 1/2 15 12.70 2.02 51.31 1.06 26.92 3/4 20 19.05 2.50 63.50 1.25 31.75 1 25 74.93 1.62 41.15	in./mm in./mm in./mm in./mm 1/4 8 6.35 1.72 43.69 0.81 20.57 0.92 23.37 3/8 10 9.53 1.79 45.47 0.93 23.62 1.05 26.67 1/2 15 12.70 2.02 51.31 1.06 26.92 1.17 29.72 3/4 20 19.05 2.50 63.50 1.25 31.75 1.40 35.56 1 25 74.93 1.62 41.15 1.76 44.70	in./mm in./mm in./mm in./mm Wt/100 1/4 8 6.35 1.72 43.69 0.81 20.57 0.92 23.37 22.00 3/8 10 9.53 1.79 45.47 0.93 23.62 1.05 26.67 29.00 1/2 15 12.70 2.02 51.31 1.06 26.92 1.17 29.72 38.00 3/4 20 19.05 2.50 63.50 1.25 31.75 1.40 35.56 54.00 1 25 74.93 2.95 74.93 1.62 41.15 1.76 44.70 110.00

6/21/2007