




65-CF7 / BN7 / CF7 / CN7 – Barbed Thru Hull Connection



Overview

Recommended for use with hose above the water line; 85-5-5 Bronze.

Dimensions



Number	Maximum Hull Thickness in./mm.	A in./mm.	B in./mm.	C in./mm.	D in./mm.	E in./mm.	F Pipe Size	G Hose Size in./mm.	WT/100*** lb./kg.
65-***7-01	1.88 47.75	2.810 71.374	4.250 107.950	2.440 61.976	1.470 37.338	1.000 25.400	1-1/4" NPSM	1.250 31.750	106.5 48.308
65-***7-02	1.88 47.75	3.060 77.724	4.250 107.950	2.380 60.452	1.500 38.100	1.250 31.750	1-1/2" NPSM	1.500 38.100	123.5 56.019
65-***7-03	1.88 47.75	2.810 71.374	4.250 107.950	2.440 61.976	1.440 36.576	0.087 2.210	1-1/4" NPSM	1.130 28.702	104 47.174
65-***7-97	1.06 26.92	1.560 39.624	3.000 76.200	1.500 38.100	1.250 31.750	0.440 11.176	1/2" NPSM	0.630 16.002	28.5 12.927
65-***7-98	1.63 41.40	1.880 47.752	3.690 93.726	2.060 52.324	1.380 35.052	0.560 14.224	3/4" NPSM	0.750 19.050	40.5 18.370
65-***7-99	1.75 44.45	2.420 61.468	3.880 98.552	2.250 57.150	1.310 33.274	0.750 19.050	1" NPSM	1.000 25.400	74 33.566

Notes

*** Weights are listed without nuts.

** Materials
 BF=Bronze fitting only
 BN=Bronze fitting with nut.
 CF=Chrome fitting only
 CN=Chrome fitting with nut