



78-200-10 Ball Type Fuel Shut-off Valve




Overview

Quality bronze valve features "mounting ears" for quick, easy installation and positive mounting. Can also be used for bonding. Available in thread sizes 1/4" - 3/4".

Features

- Surface Mounted.
- 400 PSIG Service Rating.
- All Wetted Metallic Parts Are Brass or Cast Bronze.
- Optional Tee Handle.
- Fast 90° On-Off turn.
- Tested 100 PSIG Air Under Water.
- Stainless Steel Lever And Nut.
- Optional With Stainless Steel Ball And Stem.
- RPTFE Seats and Seals

Dimensions



Number	Size	A	B	C	D	E	WT/100
	in./mm.	in./mm.	in./mm.	in./mm.	in./mm.	in./mm.	lb./kg.
78-248-10	1/4	0.430	1.120	2.250	1.780	3.870	68
	8	10.922	28.448	57.150	45.212	98.298	30.844
78-250-10	3/8	0.500	1.120	2.250	1.780	3.870	68
	10	12.700	28.448	57.150	45.212	98.298	30.844
78-256-10	1/2	0.500	1.120	2.250	1.780	3.870	65
	15	12.700	28.448	57.150	45.212	98.298	29.483
78-438-10	3/4	0.680	1.500	3.000	2.120	4.870	140
	20	17.272	38.100	76.200	53.848	123.698	63.503

